

Air Tack F *Offset Blanket*



Air Tack F 1.70

Sticky-back compressible blanket for check printing and in-lay varnishing.

The unique adhesive system allows for this 3 ply blanket to be used directly on the cylinder. Ideal for check printing, it offers superior printability, longer life and peels cleanly from the cylinders for easy removal.

Air Tack F 1.95

Sticky-back compressible blanket for two-piece can printing.

Self-adhering compressible 4 ply blanket designed for two-piece metal can printing. Eliminates time-consuming blanket changes, and offers superior print quality with longer life. Forget about messy tape, these blankets peel cleanly from the cylinder.

kinyo
VIRGINIA INC.

Air Tack F 1.70 & 1.95 Offset Blankets

Advantages

- Surface rubber is formulated to give quick release.
- Polished surface offers exact registration, excellent dot reproduction on metal substrates and reduced linting.
- Specially designed carcass with minimal gauge loss.
- Strict gauge control from blanket to blanket ensures quicker setup and perfect dot reproduction every time.
- Coating techniques require less solvent use in the rubber. This results in pinhole-free surfaces.

Typical Physical Properties

	3 Ply	4 Ply
Overall Hardness (Shore A)	77 – 83	78 – 80
Gauge	1.70 mm – 1.80 mm	1.95 mm – 2.00 mm
Tensile Strength	60 kgf/cm 59 kN/m	75 kgf/cm 74 kN/m
Surface Roughness (Ra)	0.7 µm	0.7 µm



290 Enterprise Drive
Newport News, VA 23603 U.S.A.
Phone: 1-757-888-2221 • Fax: 1-757-888-2314
www.kinyova.com

